
JM500 Self driven jet cleaner


The **JM500** belongs to the new generation of 360° jet cleaners.

It completes the product range for applications that require high impact performance as well as a higher cleansing volume for rinsing. The state-of-the-art design allows a flexible adjustment for any application of this type

|--|

JM 500 SPECIFICATION		
Max. working temp of cleansing agent	121°C	
Weight	5.2 kgs	
Cleansing agent	Water	
Working pressure	3.5 - 13 bar	
Connection	1.1/2"" BSP : NPT	
Volume	135 - 490 lpm	
Number of revolutions	5 - 20	
Number of nozzles	4	
Rec Max diam for cleaning	Up to 4mtrs ; max. 5 mtrs	
Installation position	Vertical, others upon request	
Certificates	Material and roughness Certs - optional	





F (Saparte (Sar)		
Specification		
Item No	Description	Connection
668 56 03NG Z0S0 20	Tanko JM500-G22 with 2 x 2nozzles Ø6.5mm 3.5-13bar slide bearing	1.1/2" BSP (female thread)
668 56 03NG Z0U0 20	Tanko JM500-G22 with 2 x 2nozzles Ø8.0mm 3.5-13 bar slide bearing	1.1/2" BSP (female thread)
668 56 03NG Z0V0 20	Tanko JM500-G22 with 2 x 2nozzles Ø9.5mm 3.5-13 bar slide bearing	1.1/2" BSP (female thread)
668 56 04NG Z0S0 20	Tanko JM500-G22 with 2 x 2nozzles Ø6.5mm 3.5-13 bar slide bearing	1.1/2" NPT (female thread)
668 56 04NG Z0U0 20	Tanko JM500-G22 with 2 x 2nozzles Ø8.0mm 3.5-13 bar slide bearing	1.1/2" NPT (female thread)
668 56 04NG Z0V0 20	Tanko JM500-G22 with 2 x 2nozzles Ø9.5mm 3.5-13 bar slide bearing	1.1/2" NPT (female thread)





SW = wrench key width